


DIMENSION (Unit :mm)

SIZE	øD	L	G	ød
50	101	60	27	50
65	121	67	34	65
80	131	73	42	80
100	156	73	53	100
125	187	86	65	125
150	217	98	79	150
200	267	127	102	200
250	330	146	126	250
300	375	181	153	300
350	420	184	171	350
400	483	190	197	400
450	538	203	222	450
500	593	213	248	500
550	647	220	277	550
600	697	222	295	600

NOTE

- 1) Max.150A should have 1pc of spring
- 2) EYE BOLT : 250A and above

12	EYE BOLT	S20C
11	PIN RETAINER	BSBFD
10	B-LUG BEARING	BSBFD
9	P-LUG BEARING	BSBFD
8	S-LUG BEARING	BSBFD
7	CENTER BEARING	BSBFD
6	SPRING	SUS304
5	STOP PIN	SUS304
4	HINGE PIN	SUS304
3	SEAL	NBR
2	DISC	SCS13
1	BODY	SC OR FC

11	PIN RETAINER	SUS304
10	B-LUG BEARING	SUS304
9	P-LUG BEARING	SUS304
8	S-LUG BEARING	SUS304
7	CENTER BEARING	SUS304
6	SPRING	SUS304
5	STOP PIN	SUS304
4	HINGE PIN	SUS304
3	SEAL	PTFE
2	DISC	SCS14
1	BODY	SCS14